

## PRODUCT DESCRIPTION:

**EXTERIOR FLOOR GLAZE** is a single-component clear acrylic coating. Formulated to withstand the extreme conditions of interior and exterior service such as exposure to U.V. sunlight as well as temperature fluctuations.

## PRODUCT FEATURES:

- Fast drying and easy to apply.
- Will not break down or yellow with exposure to U.V. light
- Abrasion resistant , will stand up to heavy foot traffic as well as light to medium duty vehicular traffic
- Excellent chemical resistance to salts, acids,alkalis, detergents, oils and fats
- Flexible, unaffected by temperature fluctuations and thermal shock
- Non-staining and scrubbable

## TYPICAL USES:

- Seals interior and exterior concrete and masonry (eg.concrete or interlocking brick driveways,walkways, stamped concrete, acid stains, polymer concrete overlays.)
- Cure and Seal for concrete.

## TECHNICAL DATA

|                                  |                                                                |
|----------------------------------|----------------------------------------------------------------|
| <b>COLOUR:</b>                   | Clear                                                          |
| <b>SHEEN:</b>                    | Gloss                                                          |
| <b>VOLUME SOLIDS:</b>            | 40%                                                            |
| <b>THEORETICAL COVERAGE:</b>     | 642 sqft/ US Gal<br>@ 1 mil DFT                                |
| <b>RECOMMENDED DFT:</b>          | approx. 2-4 mils/ coat                                         |
| <b>DRY TIME:<br/>@21°C(70°F)</b> | Touch 1-2 hrs<br>Light Traffic 24 hrs<br>Normal Traffic 7 days |
| <b>FLASH POINT:</b>              | 27°C(81°F)                                                     |
| <b>REDUCER:</b>                  | NPC Glaze Thinners                                             |
| <b>CLEAN UP:</b>                 | NPC Glaze Thinners                                             |